

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau(43) International Publication Date
8 March 2001 (08.03.2001)

PCT

(10) International Publication Number
WO 01/15594 A1(51) International Patent Classification⁷: A61B 3/16

(21) International Application Number: PCT/SE00/01628

(22) International Filing Date: 24 August 2000 (24.08.2000)

(25) Filing Language: Swedish

(26) Publication Language: English


(30) Priority Data:
9903099-1 31 August 1999 (31.08.1999) SE

(71) Applicants and

(72) Inventors: EKLUND, Anders [SE/SE]; Allmogevägen
10, S-905 96 Umeå (SE). LINDAHL, Olof [SE/SE];
Gökropsvägen 10H, S-906 51 Umeå (SE).(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ,
DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR,
HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR,
LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ,
NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM,
TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian
patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European
patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE,
IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG,
CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published:

— With international search report.

(74) Agents: KARLSSON, Per, Tomas et al.; AB Stockholms
Patentbyrå, Zacco & Bruhn, Box 23101, S-104 35 Stock-
holm (SE).For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.(54) Title: METHOD AND DEVICE FOR DETERMINING THE INTRAOCULAR PRESSURE, BY MEASURING THE
CHANGING OF THE FREQUENCY CHARACTERISTICS

(57) Abstract: The present invention relates to a method and a device for measuring the pressure p in an eye, the so-called intraocular pressure. The method includes a contact body with a known geometry being pressed against the eye with a gradually increasing contact force F and that when the area of deformation of the eye A can be determined, the pressure can be obtained from the relation $P=F/A$, whereby the frequency characteristic of a contact body associated with a sensor system oscillating in resonance is read, the contact body is pressed against the eye to form a new system oscillating in resonance, the contact force and frequency characteristic for the new system is read, and the change in frequency characteristic is calculated. In this way, the pressure of the eye can be determined since the sought deformation area A is a function of the change Δf (i.e. Δf is a function of A). The device has a contact body (4) for pressing against the eye (1) and a means (3) of determining the force with which the contact body is pressed against the eye, whereby the contact body (4) is part of a system oscillating in resonance, and the resonance system is connected to a means (9) for reading the frequency characteristic of the system.